



CPAP AND BIPAP MACHINES

OXYGO CPAP

OxyGo CPAP offers both traditional CPAP and APAP (Auto CPAP) modes for treating obstructive sleep apnea. A constant built in humidifier keeps users from drying out at night.

FEATURES:

- Two modes: CPAP and APAP
- Intelligent monitoring, high sensitivity
- German designed blower
- Quiet operation <30dB
- Simple, easy-to-program interface
- Large HD color display for easy operation
- Detachable humidifier
- Easy-to-clean and transport
- Warranty: 2 year unit, 1 year accessories



2100-6000

INCLUDES:

- SD Card
- 6 ft hose
- Convenient travel bag

ASK ABOUT OUR BIPAP WITH THESE FEATURES:

- Four modes: CPAP, S, T, S/T, APCV
- APCV mode: Assist pressure control
- Real-time alarm
- Lightweight: 4lbs
- Warranty: 2 year unit, 1 year accessories
- BIPAP Part Number: # 2100-6010

CONTACT US: 888-327-7301

orders@oxygo.life



REPLACEMENT PARTS:

Replacement Humidifier Chamber for C20A Auto CPAP



2100-6050

Replacement humidifier chamber for C20A CPAP device.


Replacement Power Cord/Adapter for CPAP/BiPAP



2100-6051

Replacement power cord/adapter for CPAP/BiPAP.

Replacement Filter Pack



2100-6052

Replacement filter pack for CPAP.

Replacement Micro SD Card for CPAP - 2 per pack



2100-6053

Replacement Micro SD Card for CPAP device.
Sold 2 per pack.

CONTACT US: 888-327-7301
orders@oxygo.life



CPAP AND BIPAP MACHINES

SPECIFICATIONS:

Specifications	C-20A CPAP
Screen	3.5" Color LCD
User Interface	One key operation
Pressure Range	4 - 20cmH2O, Auto Adjusting
Accuracy	±0.5cmH2O
Belex	2-4cmH2O, 3 Adjustable Levels (makes expiration more comfortable)
Ramp	0-60min
Noise Level	<30dB (10cmH2O)
Auto Switch Off	Yes
Leakage Compensation	Yes
Altitude Compensation	Yes
Titration	Yes, 95th Titration
Humidifier	0-5 Level, Water Chamber separable
SpO2	Yes, Optional
Parameter Monitor	Flow/Press/LK/BPM/SpO2 (Optional) / PR (Optional)
Real-time Alarm	Power Failure/Low Voltage/Airway Block/High Leakage/Humidifier Failure/TF Card Full
Data Download	FT Card 8G
Data Report	Available
Self-diagnostic Questionnaire	Yes
Net Weight	4.8lbs 11.02" x 7.87" x 4.41"
Gross Weight	10lbs 14.76" x 11.41" x 9.25"
Warranty	2 Years (unit), 1 year (accessories)

Specifications	B-30P BiPAP
Screen	3.5" Color LCD
Work Mode	CPAP, S/T, S, T, APCV
Inspiration Pressure	4 - 30cmH2O, Auto, 1-6 level
Expiration Pressure	4-25cmH2O
Inspiration Sensitivity	Auto, 1-6 level
VAF Function	Yes, Tidal Volume 50~2000ml
Accuracy	±0.5cmH2O
Belex	1-3 level (2-4cmH2O) (makes expiration more comfortable)
Ramp	0-60min
BPM	3-40bpm
Inspiration Time	0.5-4.0s
Auto On/Off	Auto off (when tube/mask is off), Auto on when unit detects breath
Leakage Compensation	Yes
Altitude Compensation	Yes
SpO2	Yes
Humidifier	0-5 level, water chamber separable
Parameter Monitor	Flow/Press/BPM/VT/MV/LK/InspT/SpO2 (Optional)/PR (Optional)
Realtime Alarm	Power failure/Low voltage/Airway Block/Low MV/High Leakage/Humidifier Failure/TF Card Full High Pressure/Low Pressure/Replace Filter
Data Download	TF Card 8G
Self-diagnostic Questionnaire	Yes